



ACID PRO 275

SINGLE STEP ACID CLEANER

ACID-PRO 275 is a non-phosphate dual acid cleaner formulated to remove organic and inorganic soil and scale from Racks, Cages, Pans, and Carts. Used according to product directions, ACID-PRO 275 is effective at removing a wide array of mineral deposits including urine scale, rust, and hard water films as well as organic soils such as fats, oils, and effectively penetrates and dissolves most common residues found in biotechnology, animal research labs and the food and beverage processing industries.

Used in pressure wash machines, CIP systems and in other applications where non-foaming properties are preferred or required.

Features & Benefits

- Liquid, non-phosphated detergent/ descaler.
Safe to stainless, glass, plastic and polymer surfaces.
- High solids liquid which can easily be automatically fed into systems.
Free rinsing with warm or cold water. LO-FOAM PRODUCT.
- Effectively removes mineral scale, product scale and burned scaly residue.
Effectively used for neutralization after caustic or alkali washing of or in CIP systems.

Physical Data

| | |
|----------------------|-------------------------|
| pH | 2.5~ |
| Product Type | Liquid |
| Spec. Gravity | 1.15 |
| Lbs./gal. | 9.59 |
| Foam (0=Low; 9=High) | 0 |
| Shelf Life | 10 years |
| Freeze Information | Not damaged by freezing |

Typical Processing

1. Dilute in water at desired strength.
2. Heat per process needs.



3. Automated control units can be used to monitor and feed into CIP systems for maximum efficiency.
4. Circulate as necessary to remove residue.
5. Rinse with fresh water.

Packaging

| | |
|----------------|--|
| Container Type | Poly |
| Net Units | 527.51 |
| Tare Wt. | 25 |
| Gross Wt. | 552.51 |
| DOT_Name | Not regulated by DOT Not subject to IATA Regulations for Air |
| DOT Hazard | Not regulated |
| Tariff ID | |

Use Parameters

| | |
|---------------------|-------------------|
| Concentration Range | ½-10% by volume |
| Temperature Range | Ambient to 170 F. |
| Time Range | As required |
| Agitation | Applicable |

Waste Disposal

Neutralize

Holding Tank Materials of Construction

ACID RESISTANT, STAINLESS OR POLY

Other Information

It is important that the OSHA DATA, "Material Safety Data Sheet" be carefully read and reviewed with the users of this product. OSHA data is required to be posted in the work area by law.



Testing, Operating & Trouble Shooting Data

ACID PRO 275

SINGLE STEP ACID CLEANER

10/6/10

- 1) Take A 10 MI Sample
 - 2) Add 3-5 Drops Phenol Ind.
 - 3) Add Drop By Drop Of 0.5n Caustic (naoh), Until The Color Changes From Clear To Pink. (counting The Drops)
 - 4) The Number Of Drops Multiplied By .0625 = Oz/gal
- 1oz = 16 Drops
1/2 Oz = 8 Drops
1/4 Oz = 4 Drops

Our People. Your Problem Solvers.

For more information on this process,
please call us at 203.756.5521 or email: techservice@hubbardhall.com

Hubbard-Hall holds certifications for **ISO 9001:2015**, Responsible Distribution, as accredited by the **ACD** (Alliance for Chemical Distributors) and as a **Women-Owned Small Business**, as well as maintaining an association with **Omni-Chem**¹³⁶.